



---

## Screw ceiling anchor with wire

### Short Description

---

- Two-part screw-on ceiling anchor with 1.5mm drop wire rope
- Thimble size bullet fitting matte silver finish



### **Ideal fixing for ceiling panels and lighting**


Ceiling anchors for attaching drop wires to plaster ceilings are neat, quick to install and supplied at low cost.

Suspended services in buildings such as acoustic panels, light fittings etc require rapid and reliable fixing systems combined with support wires. For lightweight building services applications 1.5mm wire cable can be relied upon to carry loads in excess of 10 kg per suspension point. These slender cables are both economical and unobtrusive.

#### **Screw ceiling anchor for conventional ceilings**

(U.SCA.1/T and U.SCA.2/T)

For plasterboard and similar conventional ceilings which will accept a plug and screw fixing, the two-part ceiling anchor is screwed to the ceiling capturing the supplied 1m or 2m length of wire.

More Information	<p><b>INSTALLATION INSTRUCTIONS</b></p> <p>The bullet shaped ceiling anchor is in two parts - the threaded shoulder which is screwed to the ceiling and the domed thimble which has a mating internal thread. Cables are supplied with a permanent termination fitting at the top end. The cable is threaded through the thimble which is then mated to the shoulder after fixing it to the ceiling (the two parts screw together by hand).</p> <p>The bottom end of the cable is supplied soldered so it will not fray when a gripper hook or similar self locking fitting is threaded onto the cable. It should only be trimmed to length using sharp wire cutters once the item has been suspended at the correct height. Surplus wire can be discarded.</p>
Product Dimensions	<p><b>Screw Ceiling Anchor</b></p>  <p>The diagram shows a 3D perspective of a domed thimble. It has a cylindrical shape with a domed top. A horizontal dimension line at the top indicates a width of 12 mm. A vertical dimension line on the left indicates a height of 17 mm. A small vertical rod or cable end is shown protruding from the bottom center of the thimble.</p>
Delivery and Returns	<ul style="list-style-type: none"><li>• We offer a choice of delivery options tailored to the goods selected and your location, calculated for you automatically in the Checkout. When feasible, you will be offered options for Free, Economy or Next Day delivery.</li><li>• Any product returned by the purchaser must be unused and in its original packaging, which should be unmarked. If goods are received damaged or faulty we will take care of the problem.</li><li>• For detailed information about Delivery charges or Returns and refund policies, please click on the links below.</li></ul>
Include in Google Feed	Yes
Postable	No
Small parcel	No
Oversize	No

