



Suspension hooks self locking

Short Description

- Choice of 3 adjustable height suspension hooks for use with 1.5mm thick wire rope.
- Suspension hooks are self locking. For adjustment press the button at the cable entry point.

Product Images





Description

Suspension hooks are adjustable

Suspension hooks with self-locking facility are ideal for rapid installation and levelling up on site.

Slide the hook up a support wire (usually 1.5mm dia) and it locks fast wherever it is placed. To lower simply depress the quick release button as shown on the image. The clutch mechanism is released until the suspended item is at exactly the right height. Excess wire can then be snipped off.

It is much easier to level up acoustic panels, light fittings and ceiling hung building services when the adjustment can be performed at the suspension point rather than at the ceiling.




- **Straight hook** is suitable for hanging vertical baffles such as a panel with a suspension hole
- **Safe Hook** has a spring catch across the mouth of the hook to prevent accidental detachment.
- **Bee-line Hook** also has a safety catch and is suitable for heavier loads than the safe hook

More Information

Product Dimensions

Need complete kits?
Not the exact fitting you require?
See [OUR FULL RANGE OF WIRE SUSPENSION KITS](#)

More Details about these suspension hooks
Excess wire should be trimmed with good quality sharp wire cutters to prevent fraying. The wire should only be trimmed once the height of the suspended item has been checked and finalised.
Safe Hook has a safe working load of 6kg
Bee-Line Hook has a safe working load of 15kg
These load ratings include a 5:1 margin of safety and apply when used with a 7x7 construction wire rope with a 1.5mm diameter.



Delivery and Returns

• We offer a choice of delivery options tailored to the goods selected and your location, calculated for you automatically in the Checkout. When feasible, you will be offered options for Free, Economy or Next Day delivery.
• Any product returned by the purchaser must be unused and in its original packaging, which should be unmarked. If goods are received damaged or faulty we will take care of the problem.
• For detailed information about Delivery charges or Returns and refund policies, please click on the links below.

Include in Google Feed

Yes

Postable

No

Small parcel

No

Oversize

No

