

Cable window displays for A3 A2 A1 - Gripper kits

Short Description

- Cable window displays for wall mounted or floor-to-ceiling A3, A2 or A1 poster pockets
- Top and bottom cable brackets have 2-way swivel feature with easy cable tensioning
- Gripper cable kits come with finger-tip-adjustable perspex print holders

Product Images



Description

Cable window display systems for A3, A2 and A1

Our cable displays for larger poster sizes feature contemporary styling - with unique finger-tip-adjustable silver fittings to secure acrylic holders in A3, A2 and A1 poster sizes. Easy level adjustment is a feature of our Gripper cable kits. (Alternative [kits are available for A4 paper](#)).

Cable window display systems to display posters are often fitted ceiling to floor, for example in showroom windows. Green Magic cable kits adapt equally to wall displays of A1 advertisements, A2 posters or A3 prints. In each size we supply portrait poster pockets. (Landscape available on longer lead time subject to minimum order quantities - please call)

Wall mounted cable systems to display posters

- Window cable display systems are popular for displaying posters behind the glass in shop windows.
- Our unique swivel brackets attach easily to almost any wall - for example above a shop window when the ceiling is not suitable to take a load bearing fixing. Stylishly designed, these fixings have an inbuilt cable tensioner at the top and convenient cable gripper at the bottom.
- Each kit comes with the required number of fixing brackets and 4m cables to complete the installation. Excess cable can be trimmed after installation.
- The appropriate number of portrait A1, A2 or A3 rigid clear plastic pockets are supplied, the quantity and layout depending on the kit ordered.
- In our **Gripper** kits the small silver side-fixings which attach the pockets to the wires have in-built cable grippers to attach the pocket to the cable. Alternative **Classic** kits require grub screws to be tightened onto the cables.

Floor-to-ceiling installation using these universal kits

- Thanks to our inventive 2-way cable fixing brackets, the same kit works equally well running from floor to ceiling - often used this way in bank windows, in fashion shops or greetings card retailers.
- The bottom cable anchor point could be secured to the floor with the top attached to the wall above a window - our system is very adaptable, as well as being very attractively styled and excellent value.

Successful installation requires competent DIY skills OR can be left to a qualified trades person. Please refer to the Assembly and Installation section on this page for further guidance.

More Information

Gripper versus Classic cable kits

The kits on this page are our Gripper cable display kits which are convenient for adjusting the position of pockets. In our Gripper kits height adjustment is achieved with a push button device built into the side fittings.

With our Classic kits the side fittings to secure A4 acrylic pockets onto the wires attach using two gub screws - one to hold the acrylic pocket and the other to attach the pocket to the cable and set the height. View [Classic Kits](#), which are slightly cheaper with especially unobtrusive side fixings.

Product Dimensions

Space required to install a cable display system with 2 or 3 bays

The width depends on the size of pockets ordered and the number bays. Multiply the nominal pocket width by the number of bays. The nominal width makes an allowance for cable fittings and visual clearance.

A3 nominal width: 40 cm

A2 nominal width: 50 cm

A1 nominal width: 70 cm

The height is very flexible as the supplied cables are 4m long (the average room is about 3m high) and the pockets can be positioned anywhere up and down the cables.

However please consider readability: poster pockets below knee height or above head height are not going to be easy to read.

Setting out dimensions

Exact setting out dimensions are shown in the diagrams supplied with your order. Note that end bays and intermediate bays have fractionally different centre to centre fixing hole dimensions.

Assembly and Installation

Installing cable displays

Successful installation requires the ability to drill into walls, floors or ceilings with precision to ensure cables end up vertical and correctly spaced apart. Screws and plastic plugs are supplied for typical installations but the installer should be able to assess any special fixing requirements due to individual site circumstances. They should also be used to considering whether buried electric cables or pipes might cause issues. We suggest that installation is carried out by a trades person or competent DIYer.

How anchors are fixed to wall, floor or ceiling

Swivel anchors comprise a threaded circular base plate which is attached to the wall, floor or ceiling using a single screw, plus the main body which then twists onto the base plate. This provides a concealed fixing. The swivel feature means that the same fitments can be used on a vertical surface (wall) or horizontal surface (ceiling or floor) or angled surface (sloping ceiling).

How cables are tensioned

The supplied cables are 4m long 1.5mm diameter galvanised wire with a termination at one end. The wires are very strong provided that the top and bottom anchors are fixed securely into a wall or ceiling capable of providing a suitable anchoring point.

To achieve taut cables there is a threaded adjustment in the top anchor fitting - a threaded barrel containing a small spring to compensate for any cable stretch over time. Initially the cable should be pulled tight from the opposite end with a few threads showing at the top anchor. The cable is gripped by the bottom anchor which has a convenient in built cable gripper. Initial tension is achieved by pulling taut. Final tension is achieved by winding up the threaded barrel at the top anchor. (The anchors can also be reversed to enable tensioning from the bottom if preferred).

The supplied cables are 4m long so normally there is excess cable to be trimmed off once the cables are all fitted and correctly tensioned. Always leave a short tail visible so cables can be re-tensioned if required.

Tools typically required

We supply all fittings and parts including allen keys and screws. The installer is likely to require the following tools:

Tape measure and pencil

Spirit level and plumb line (plumb bob)

Electric drill and masonry drill bits

Cross-head screwdriver

Wire cutters to trim off excess cable. We sell [good quality wire cutters](#).

Delivery and Returns

- We offer a choice of delivery options tailored to the goods selected and your location, calculated for you automatically in the Checkout. When feasible, you will be offered options for Free, Economy or Next Day delivery.
- Any product returned by the purchaser must be unused and in its original packaging, which should be unmarked. If goods are received damaged or faulty we will take care of the problem.
- For detailed information about Delivery charges or Returns and refund policies, please click on the links below.