

Glazed partition screen booth divider

Short Description

- Floor standing glazed partition screen 2m high with narrow end to fit into restricted spaces
- Booth divider, also used as vending machine separators or slot machine partitions
- Full size foot one end with multi-use wall clips provided to stabilise the narrow end

Product Images



Narrow-end divider for restricted spaces

This clear light-weight plastic glazed partition is specially adapted for use as a freestanding booth divider or protective screen when there is only a limited gap between machines or furniture, where side-by-side placement requires a physical barrier to shield adjacent persons against possible cross-infection.

- The narrow end screen is an ideal solution when social distancing is required between one-arm bandits or slot machines in a casino or amusement arcade, between self service checkouts, wash basin vanity units, urinal stalls or machinery in a workshop.
- Based on our popular floor standing protection screens, with this booth divider version one of the flat bar feet is replaced by a single-point foot. The three contact points with the floor can be used with standard rubber glide feet or fitted with castors for additional mobility.
- Our 2m high by 1m wide glazed dividers are available with silver or black surrounds.
- The light gauge rigid clear plastic glazing is supplied ready-mounted in the aluminium frame.

Multi-purpose wall clips are included

Without additional support the narrow end would be less stable. So our glazed partition booth divider is supplied with multi-use wall clips.

- The pair of clips can either be screwed or stuck directly to the back wall, spaced vertically so that the narrow-end frame surround engages into it with a snug push fit. Spacer blocks (not supplied) may be required to adjust for the thickness of skirting boards.
- Sometimes the partition only needs to penetrate a short distance into the gap - for example between vending machines or one-arm bandits. In this case the strong adhesive tape fixing option can be applied to the side of each clip, allowing the clips to be stuck securely onto the side of one machines.
- The metal wall clips are lined with EVA foam. This means that the frame surround is a snug push fit into the clip. The divider can be removed or re-positioned while leaving the clips in place.
- Additional sets of wall clips are available in the event that multiple locations need to be enabled for use with screens which can then be positioned on-demand.
- The clips should be spaced apart to hold the upright member stable, but the exact positions are not critical provided the clips are aligned correctly.

More Information

What's included?

- In each kit you will receive a standard floor protection screen glazed with light gauge 1mm thick optically clear PET plastic.
- Each frame is supplied with two flat-bar feet. One of the feet is not required in this particular configuration (but can be retained in case you decide to reconfigure the unit later on as a standard freestanding screen).
- A small rectangular single-point foot replaces one of the normally protruding flat bar feet.
- If ordered with wheels you may receive a set of 4 locking castors - but you only need 3 of them unless you later revert to the standard configuration. (Exception is for orders for multiple narrow-end screens - in this case we will include the exact number of castors needed).
- With each kit you will receive a pair of metal foam-lined wall clips, colour coordinated to match the frame, complete with screws and wall plugs; and also including twin adhesive tape strips for use if you intend to stick-on the clips rather than screwing them

Glazed partition for restricted spaces | Slot machine partition | Casino distancing screen | Includes wall clips for stability.

Product Dimensions

The minimum gap width to fit a narrow-end screen is 5cm. The nominal height of the divider screen is 2m, plus approximately 80 cm when wheels are ordered. The width of the screen panel is 1m.

Assembly and Installation

The clear PET screen (1mm thick) is supplied pre-mounted in the aluminium surround. It can be removed for cleaning but this is rarely required as it can be cleaned in situ. All that is required is to attach the feet (one bar foot and one small foot), fasten the glides or castors (if ordered with wheels) and fix the pair of support clips to the wall or an adjacent flat face (such as the side of a machine). Instructions are supplied.

Delivery and Returns

- We offer a choice of delivery options tailored to the goods selected and your location, calculated for you automatically in the Checkout. When feasible, you will be offered options for Free, Economy or Next Day delivery.
- Any product returned by the purchaser must be unused and in its original packaging, which should be unmarked. If goods are received damaged or faulty we will take care of the problem.
- For detailed information about Delivery charges or Returns and refund policies, please click on the links below.